

## > EZ CLEANER

Multipurpose Primer for Waterproofing, Repair & Surface Preparation

### Description

EZ CLEANER is a high-quality, fast-acting acid-based cleaner and degreasing solution designed for the regular daily maintenance of dirt and stains on tile surfaces. It is highly effective for the rapid removal of whitish spots, water stains, cement stains, grime, oil, paint stains, grease, moss, and wax

### Fields of application

- Can be used directly or easily diluted with water for routine cleaning.
- Quickly removes difficult and stubborn stains.
- Easily removes soaps, scum, efflorescence, and mineral deposits.
- Protects the color and shine of tiles without damaging joints between ceramic tiles, including those grouted with colored products.
- Ideal for both interior and exterior cleaning applications.

### Features and Benefits

EZ CLEANER is suitable for domestic, commercial, internal, and external tiling areas, including kitchens, bathrooms, toilets, garages, factories, and general building sites. Suitable substrates include:

- Unglazed and Glazed Ceramic Tiles.
- Vitrified Tiles and Porcelain Tiles.
- Glass Tiles and Glass Mosaic Tiles.
- Sanitaryware.
- Concrete, asbestos, and terrazzo (specifically for removing moss and wax).

### Technical Data

Appearance	Free Flowing Liquid
Density / Specific Gravity	Approximately 1.02 g/ml
pH value	<2
Soaking Time	2 to 5 min

### Application Procedure

- Shake the container well for one minute before opening for use.
- For routine cleaning: Dilute two capfuls of EZ CLEANER with half a bucket of water.
- For mild blemish spots: Mix the cleaner with water in a 1 : 1 proportion. Soak a cloth or sponge in the solution and rub the surface until the spots are removed.
- For stubborn stains: Pour the neat liquid (without dilution) directly onto the stained surface. Let it stand for 2-3 minutes to react with the stain.
- Use a scrub pad to rub the surface, adding a little more liquid if it feels dry.
- Rinse thoroughly with plain water and repeat the procedure if needed.

### Consumption

Coverage depends heavily on the porosity of the surface and the intensity of the stains.

### Packaging

1 ltr, 5lt

### Storage

12 months in original, unopened package.

### Shelf Life

Store in dry area between +5°C and +35°C. Protect from heat, freezing and direct sunlight

### Cleanup Information

Clean tools and equipment with water immediately after use.

### Cautions/Limitations

- Always check the cleaner in a small corner test area before using it on colored concrete, granite, marble, or other natural stones, as acidic cleaners may etch, lighten, or discolor the surface. If discoloration occurs within 24 hours, do not use the product.
- Avoid contact with metals, wood, carpet, and landscaping. Do not mix with ammoniated cleaners, as harmful fumes may result.
- Allow new epoxy grout to cure fully according to the manufacturer's specifications before use. Contact with cement-based grouts may alter their color or performance.
- This is an acidic-based cleaner. Wear suitable protective clothing, hand gloves, a nose cover, and eye protection during use. In case of skin or eye contact, rinse immediately with plenty of clean water and seek medical advice. Keep out of reach of children.

### Health and Safety

**Warning!** Cause eye and skin irritation. If eye or skin contact, get immediate medical attention. If swallowed, do not induce vomiting. Call a physician or poison control center. Never give anything by mouth to an unconscious person.

Wash hands thoroughly after handling. Wear protective clothing, gloves, eye and face protection.

Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. Dispose of unused, contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

Keep container closed when not in use. Keep out of the reach of children.

**Limited Warranty:** This product is subject to a written limited warranty which can be obtained free of charge from Carbosil Company. Please contact with technical service department for further information and support.